



NIPEX INDIA

COMMITMENT TO EXCELLENCE

WEBSITE:

www.nipexindia.com

CONTACT US :

9654442247



OZONE 500



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux
Number of LED	48
Focus Size	100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	3500-5200 kelvin
Endo and Memory Mode	Inbuilt
Power Supply	220V/ 50Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light
- 360 Rotation Arm



Ozone 500+500



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux + 160000
Number of LED	48 + 48
Focus Size	100-250mm + 100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours + >50000 Hours
Colour Rendering Index (CRI)	92 Ra + 92 Ra
Colour Temperature (K)	3500-5200 kelvin + 3500-5200 Kelvin
Endo and Memory Mode	Inbuilt + Inbuilt
Power Supply	220V/ 50Hz AC + 220V / 50 Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light
- 360 Rotation Arm

Ozone 500 M



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux
Number of LED	48
Focus Size	100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	3500-5200 kelvin
Endo and Memory Mode	Inbuilt
Power Supply	220V/ 50Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light

GRAND 500



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux
Number of LED	48
Focus Size	100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	3500-5200 kelvin
Endo and Memory Mode	Inbuilt
Power Supply	220V/ 50Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light
- 360 Rotation Arm



GRAND 500 + 500



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux + 160000
Number of LED	48 + 48
Focus Size	100-250mm + 100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours + >50000 Hours
Colour Rendering Index (CRI)	92 Ra + 92 Ra
Colour Temperature (K)	3500-5200 kelvin + 3500-5200 Kelvin
Endo and Memory Mode	Inbuilt + Inbuilt
Power Supply	220V/ 50Hz AC + 220V / 50 Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light
- 360 Rotation Arm

GRAND 500 M



Optional :  Camera  Battery Backup

TECHNICAL SPECIFICATIONS

Intensity	160000 Lux
Number of LED	48
Focus Size	100-250mm
Focus Adjustment	Variable
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	3500-5200 kelvin
Endo and Memory Mode	Inbuilt
Power Supply	220V/ 50Hz AC

SPECIAL FEATURES

- Aluminum Body
- Dome Dia 500mm
- OSRAM LED
- Sterilizable handle
- Endoscopy Mode
- Wireless Remote
- Compact Design
- Shadowless light

CRYSTAL



SPECIAL FEATURES

- Flexible Gooseneck 360
- Shadow less light
- Polycarbonate body
- Osram led
- Compact design
- Screw less dome

TECHNICAL SPECIFICATIONS

Intensity	80000 Lux
Number of LED	14 LED
Focus Size	100MM
Focus Adjustment	Variable
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	5000 K
Endo and Memory Mode	Not Applicable
Power Supply	220V/ 50Hz AC

Glow



TECHNICAL SPECIFICATIONS

Intensity	40000 Lux
Number of LED	3 LED
Focus Size	100MM
Focus Adjustment	Fixed
LED Life Span	>50000 Hours
Colour Rendering Index (CRI)	92 Ra
Colour Temperature (K)	5000 K
Endo and Memory Mode	Not Applicable
Power Supply	220V/ 50Hz AC

SPECIAL FEATURES

- Flexible Gooseneck 360
- Shadowless light
- Polycarbonate body
- Osram led
- Compact design



MODEL
VITA

C-ARM GEAR MATIC

STANDARD ACCESSORIES

- Arm Rest -2 pcs.
- Try Handle -1 pcs.
- Pu Mattress -1 Set
- Body Support -2 Pcs. Leg
- Support -2 pcs
- Anesthetic Rod - 1 pcs
- Shoulder Support - 2pcs

FEATURES

- HYDRAULIC AND MECHANICAL OPERATED.
- LEG ANG HEAD SECTION ARE INTERCHANGABLE.
- BASE IS ENCENTRIC FOR TROUBLE FREE C-ARM MOVEMENTS.
- INBUILD KIDNEY BRIDGE.
- FIVE SECTIONAL RADIO-TRANSLUCENT.
- MANUAL FLOOR LOCKING
- SYSTEM. BASE AND COVER MADE OF ATTRACTIVE, EASY TO CLEAN STAINLESS STEEL.

TECHNICAL SPECIFICATIONS

Length of Table	1900 mm
Width of Table Top	535 mm
Minimum Height	Min.730 mm
Maximum Height	Max.980 mm
Lateral Tilt	20° / 20°
Leg Section	+20° /- 90°
Head	+45° / -90°
Back Section Trend/Reverse Trend	+ 75° /-25° °30 /30°



MODEL
SIGMA

C Arm compatible Semi Electric

STANDARD ACCESSORIES

- Arm Rest -2 pcs.
- Try Handle -1 pcs.
- Pu Mattress -1 Set
- Body Support -2 Pcs. Leg Support- 2 pcs Anesthetic Rod - 1 pcs
- Shoulder Support - 2pcs

FEATURES

- REMOTE AND MECHANICAL OPERATED.
- LEG AND HEAD SECTION ARE INTERCHANGABLE.
- BASE IS ECCENTRIC FOR TROUBLE FREE C-ARM MOVEMENTS.
- INBUILT KIDNEY BRIDGE.
- FIVE SECTIONAL RADIO-TRANSLUCENT.
- MANUAL FLOOR LOCKING SYSTEM. BASE AND COVER MADE OF ATTRACTIVE, EASY TO CLEAN STAINLESS STEEL.


TECHNICAL SPECIFICATIONS

Length of Table	1900 mm
Width of Table Top	535 mm
Minimum Height	Min.730 mm
Maximum Height	Max.980 mm
Lateral Tilt	20° / 20°
Leg Section	+20° / - 90°
Head	+45° / -90°
Back Section Trend/Reverse Trend	+ 75° /-25° °30 /30°



NIPEX INDIA

COMMITMENT TO EXCELLENCE



Follow us everywhere!

Manufacturer By :

NIPEX INDIA

G-84, SECTOR-4
BAWANA INDUSTRIAL AREA
DELHI-110039